

tesapack® eco & strong

- Sturdy with strong PP-backing
- High sealing security
- Even, low-noise unwinding
- High UV-resistance
- Suitable for use with all tesapack® hand dispensers

Ecological features:

- Backing: 100% recycled plastic
- Core :100% recycled cardboard
- Solvent-free adhesive

Main Application

- For secure packaging

Technical Data & Properties

Dimensions	66m : 50mm
Product structure	Single-sided
Colour	IBNR / sort 58153 – Transparent IBNR / sort 58154 – Brown IBNR / sort 58155 – Brown-Printed IBNR / sort 58156 – Green-Printed
Type of Adhesive	Waterbased Acrylic
Adhesion/Steel	2,5 N/cm
Type of Backing	Polypropylene (PP)
Total Thickness	56 µm
Tensile Strength	40 N/cm
Elongation at break	> 80%

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Additional Information & Exemplary representation



58153



58154



58155



58156

IBNR's

IBNR	Article Description
58153	TESAPACK ECO & STRONG 66:50 TRANSPARENT LABEL
58154	TESAPACK ECO & STRONG 66:50 BROWN LABEL
58155	TESAPACK ECO & STRONG 66:50 BROWN PRINTED
58156	TESAPACK ECO & STRONG 66:50 GREEN PRINTED

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.